



MODEL NO.: NFS-30  
 DRAWING NO.: C-19320  
 DESCRIPTION: NFS WITH STANDARD SPRING FOR FLOW RATES OF 6 OR MORE DROPS PER MINUTE.

NFS-30L  
 DRAWING NO.: C-19320-L  
 DESCRIPTION: NFS WITH LIGHT SPRING FOR FLOW RATES BETWEEN 3 AND 6 DROPS PER MINUTE.

NOTE: SWITCH MUST BE MOUNTED TERMINAL END UP WITH A MINIMUM ANGLE OF 20° OFF HORIZONTAL TO PREVENT CONDENSATION AROUND SWITCH CONTACT.

INFORMATION IS PROPRIETARY TO KENCO ENGINEERING CO.

TOLERANCES UNLESS OTHERWISE SPECIFIED  
 DECIMAL: ±.005" FRACTIONAL: ±1/64" ANGULAR: ±1/2°

KENCO ENGINEERING COMPANY  
 TULSA, OKLAHOMA

SWITCH, NO FLOW  
 MODEL NFS-30 / NFS-30L

REV.	DATE	BY	CHKD.	ECN	EXPLANATION:
A	02-20-96	TW		N/A	ITEM 9 WAS ZINC PLATED CARBON STEEL
B	10-15-96	TW		N/A	O-RING SEALS AND BACK-UP RING MATERIAL WAS BUNA-N
C	03-11-05	RDM		N/A	ITEM 13 P/N WAS A-19332
D	08-30-12	DS	KI	000058	REDRAWN; WAS HAND DWG; ADDED SHEET 2; ADDED NFS-30L; RING TERMINAL WAS 16-14

DATE: 02-05-93  
 DRN. BY: RC  
 SCALE: 1-1/2"=1"

SHEET: 1 OF 2  
 CHKD. BY:  
 REVISION: D

DRAWING NUMBER  
 C-19320  
 C-19320-L