



MODEL NO.: KEFS-2-DPDT4-S6

**SPECIFICATIONS:**

SWITCH RATING: 4A @ 125/250 VAC  
5A @ 30 VDC

CONTACT TYPE: DPDT  
MINIMUM OPERATING S.G.: .53  
MAX. WORKING PRESSURE: 2000 PSI  
WETTED MATERIALS: 316 STAINLESS STEEL

			DIM'S IN INCHES TOLERANCES UNLESS OTHERWISE SPECIFIED.		 Tulsa, Oklahoma USA	MATERIAL:	SEE B/M	
			RELEASED			RELEASE LEVEL:	RELEASED	
REV.	DATE	DRN.	DESCRIPTION			DRAWING CREATED IN PRO/ENGINEER		
	ECN	CHKD.				TITLE: SWITCH, ELECTRIC FLOAT, 2000 PSI, 4A DPDT KEFS 316 S.S. (OUTLINE DRAWING)		
<b>PROPRIETARY:</b> THIS DRAWING AND THE INFORMATION CONTAINED HEREIN IS PROPRIETARY TO KENCO ENGINEERING CO. AND SHALL NOT BE REPRODUCED, COPIED, OR DISCLOSED IN WHOLE OR IN PART, OR USED FOR MANUFACTURE OR FOR ANY OTHER PURPOSE WITHOUT THE WRITTEN PERMISSION OF KENCO ENGINEERING.			ANGULAR ±1/2° FRACTIONAL ±1/64" (X.X) ±0.015" (X.XX) ±0.010" (X.XXX) ±0.005" MACH FILLET RAD: .031" 125 MAX. FINISH, ALL MACHINED SURFACES.		DRN. BY: BRC	SCALE: 0.750	DRAWING NUMBER 58084	
					CHKD. BY: DS	REVISION: A		
					DATE: 4/15/09	SHEET 1 OF 3		