



MODEL NO.: KEFS-2-DPDT4

SPECIFICATIONS:

SWITCH RATING: 4A @ 125/250 VAC  
 5A @ 30 VDC  
 CONTACT TYPE: DPDT  
 MINIMUM OPERATING S.G.: .53  
 MAX. WORKING PRESSURE: 2000 PSI  
 WETTED MATERIALS: 303/304 STAINLESS STEEL.

			DIM'S IN INCHES TOLERANCES UNLESS OTHERWISE SPECIFIED.		 Tulsa, Oklahoma USA	MATERIAL:	SEE B/M		
			ANGULAR ±1/2° FRACTIONAL ±1/64" (X.X) ±0.015" (X.XX) ±0.010" (X.XXX) ±0.005" MACH FILLET RAD-.031" 125 MAX. FINISH, ALL MACHINED SURFACES.			RELEASE LEVEL:	RELEASED		
REV.	DATE	DRN.	RELEASED DESCRIPTION		DRAWING CREATED IN PRO/ENGINEER				
	ECN	CHKD.			TITLE: SWITCH,ELECTRIC FLOAT,2000 PSI 4A DPDT KEFS (OUTLINE DRAWING)		DRN. BY:	BRC	SCALE:
<b>PROPRIETARY:</b> THIS DRAWING AND THE INFORMATION CONTAINED HEREIN IS PROPRIETARY TO KENCO ENGINEERING CO. AND SHALL NOT BE REPRODUCED, COPIED, OR DISCLOSED IN WHOLE OR IN PART, OR USED FOR MANUFACTURE OR FOR ANY OTHER PURPOSE WITHOUT THE WRITTEN PERMISSION OF KENCO ENGINEERING.					CHKD. BY:	DS	REVISION:	A	57557
					DATE:	01/14/09	SHEET 1 OF 3		