


MODEL NO.: KEFS-2-SPDT5-S6

SPECIFICATIONS:

SWITCH RATING: 5A @ 125/250 VAC
5A @ 30 VDC

CONTACT TYPE: SPDT
MINIMUM OPERATING S.G.: .53
MAX. WORKING PRESSURE: 2000 PSI
WETTED MATERIALS: 316 STAINLESS STEEL

				DIM'S IN INCHES TOLERANCES UNLESS OTHERWISE SPECIFIED.		 KENCO ENGINEERING Tulsa, Oklahoma USA		MATERIAL: SEE B/M	
				ANGULAR ±1/2° FRACTIONAL ±1/64" (X.X) ±0.015" (X.XX) ±0.010" (X.XXX) ±0.005" MACH FILLET RAD: .031" 125 MAX. FINISH, ALL MACHINED SURFACES.				RELEASE LEVEL: RELEASED	
A	4/6/09	BRC		RELEASED		TITLE: SWITCH, ELECTRIC FLOAT, 2000 PSI, 5A SPDT KEFS 316 S.S. (OUTLINE DRAWING)			
REV.	DATE	DRN.				DRN. BY: BRC		SCALE: 0.750	DRAWING NUMBER
	ECN	CHKD.		DESCRIPTION		CHKD. BY: DS	REVISION: A	58083	
PROPRIETARY: THIS DRAWING AND THE INFORMATION CONTAINED HEREIN IS PROPRIETARY TO KENCO ENGINEERING CO. AND SHALL NOT BE REPRODUCED, COPIED, OR DISCLOSED IN WHOLE OR IN PART, OR USED FOR MANUFACTURE OR FOR ANY OTHER PURPOSE WITHOUT THE WRITTEN PERMISSION OF KENCO ENGINEERING.						DATE: 4/6/09	SHEET 1 OF 3		