

MODEL NO.: KEFS-2-SPDT5

SPECIFICATIONS:


SWITCH RATING: 5A @ 125/250 VAC
5A @ 30 VDC

CONTACT TYPE: SPDT

MINIMUM OPERATING S.G.: .53

MAX. WORKING PRESSURE: 2000 PSI

WETTED MATERIALS: 303/304 STAINLESS STEEL.

			DIM'S IN INCHES TOLERANCES UNLESS OTHERWISE SPECIFIED.		 KENCO ENGINEERING Tulsa, Oklahoma USA	MATERIAL:	SEE B/M		
			RELEASED			RELEASE LEVEL:	RELEASED		
REV.	DATE	DRN.	DESCRIPTION			DRAWING CREATED IN PRO/ENGINEER			
	ECN	CHKD.				TITLE:		SWITCH, ELECTRIC FLOAT, 2000 PSI 5A SPDT KEFS (OUTLINE DRAWING)	
PROPRIETARY: THIS DRAWING AND THE INFORMATION CONTAINED HEREIN IS PROPRIETARY TO KENCO ENGINEERING CO. AND SHALL NOT BE REPRODUCED, COPIED, OR DISCLOSED IN WHOLE OR IN PART, OR USED FOR MANUFACTURE OR FOR ANY OTHER PURPOSE WITHOUT THE WRITTEN PERMISSION OF KENCO ENGINEERING.			ANGULAR $\pm 1/2^\circ$ FRACTIONAL $\pm 1/64"$ (X.X) $\pm 0.015"$ (X.XX) $\pm 0.010"$ (X.XXX) $\pm 0.005"$ MACH FILLET RAD: .031" 125 MAX. FINISH, ALL MACHINED SURFACES.		DRN. BY:	BRC	SCALE:	0.750	DRAWING NUMBER
					CHKD. BY:	DS	REVISION:	A	
					DATE:	01/09/09	SHEET 1 OF 3	57486	