


MODEL NO.: KEFS-2-SPDT8-S6

SPECIFICATIONS:

SWITCH RATING: 8A @ 125/250 VAC
 12A @ 125 VAC RESISTIVE
 CONTACT TYPE: SPDT
 MINIMUM OPERATING S.G.: .53
 MAX. WORKING PRESSURE: 2000 PSI
 WETTED MATERIALS: 316 STAINLESS STEEL

				DIM'S IN INCHES TOLERANCES UNLESS OTHERWISE SPECIFIED.		 KENCO ENGINEERING Tulsa, Oklahoma USA		MATERIAL: SEE B/M	
				ANGULAR ±1/2° FRACTIONAL ±1/64" (X.X) ±0.015" (X.XX) ±0.010" (X.XXX) ±0.005" MACH FILLET RAD: .031" 125 MAX. FINISH, ALL MACHINED SURFACES.				RELEASE LEVEL: RELEASED	
A	4/15/09	BRC		RELEASED		TITLE: SWITCH, ELECTRIC FLOAT, 2000 PSI, 8A SPDT KEFS 316 S.S. (OUTLINE DRAWING)			
REV.	DATE	DRN.				DESCRIPTION		DRN. BY: BRC	SCALE: 0.750
	ECN	CHKD.				CHKD. BY: DS	REVISION: A	58085	
PROPRIETARY: THIS DRAWING AND THE INFORMATION CONTAINED HEREIN IS PROPRIETARY TO KENCO ENGINEERING CO. AND SHALL NOT BE REPRODUCED, COPIED, OR DISCLOSED IN WHOLE OR IN PART, OR USED FOR MANUFACTURE OR FOR ANY OTHER PURPOSE WITHOUT THE WRITTEN PERMISSION OF KENCO ENGINEERING.						DATE: 4/15/09	SHEET 1 OF 3		