



MODEL NO.: KEFS-2-SPDT8

SPECIFICATIONS:

SWITCH RATING: 8A @ 125/250 VAC
 12A @ 125 VAC RESISTIVE
 CONTACT TYPE: SPDT
 MINIMUM OPERATING S.G.: .53
 MAX. WORKING PRESSURE: 2000 PSI
 WETTED MATERIALS: 303/304 STAINLESS STEEL.

			DIM'S IN INCHES TOLERANCES UNLESS OTHERWISE SPECIFIED.		 Tulsa, Oklahoma USA	MATERIAL:	SEE B/M	
			ANGULAR ±1/2° FRACTIONAL ±1/64" (X.X) ±0.015" (X.XX) ±0.010" (X.XXX) ±0.005" MACH FILLET RAD: .031" 125 MAX. FINISH, ALL MACHINED SURFACES.			RELEASE LEVEL:	RELEASED	
A	01/14/09	BRC	RELEASED				DRAWING CREATED IN PRO/ENGINEER	
	N/A	DS						
REV.	DATE	DRN.	DESCRIPTION				TITLE:	
	ECN	CHKD.						
PROPRIETARY: THIS DRAWING AND THE INFORMATION CONTAINED HEREIN IS PROPRIETARY TO KENCO ENGINEERING CO. AND SHALL NOT BE REPRODUCED, COPIED, OR DISCLOSED IN WHOLE OR IN PART, OR USED FOR MANUFACTURE OR FOR ANY OTHER PURPOSE WITHOUT THE WRITTEN PERMISSION OF KENCO ENGINEERING.			DRN. BY: BRC CHKD. BY: DS DATE: 01/14/09		SCALE: 0.750 REVISION: A SHEET 1 OF 3	DRAWING NUMBER 57558		