



GENERAL NOTES:

1. WETTED MATERIALS: 316 STAINLESS STEEL AND PTFE.
2. MANIFOLD IS SHIPPED UNASSEMBLED.
3. KENCO RECOMMENDS THE USE OF PTFE TAPE OR A SERVICE COMPATIBLE PIPE THREAD COMPOUND DURING ASSEMBLY TO ENHANCE SEALING AND PREVENT GALLING.
4. DRAWING REPRESENTS AN ASSEMBLED MANIFOLD KIT WITH 1/4" FNPT OUTLET CONNECTION ON RIGHT-HAND SIDE.
5. MANIFOLD WITH 1/4" FNPT OUTLET ON LEFT-HAND SIDE CAN BE MADE BY ASSEMBLING 3/4" NPT BALL VALVE AND PIPE CAP ON OPPOSITE SIDES.
6. DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY AND ARE SUBJECT TO CHANGE AT ANY TIME WITHOUT NOTICE.
7. REFER TO KENCO DRAWING 69346 FOR INSTALLATION INSTRUCTIONS.

KMK-75-F

INFORMATION IS PROPRIETARY TO KENCO ENGINEERING CO.

REV.	DATE	BY	CHKD.	ECN	EXPLANATION:
A	02-17-17	RDM	KLM	N/A	ADDED U.S. PATENT NUMBER 9,546,897

KENCO ENGINEERING COMPANY TULSA, OKLAHOMA		
KIT, MANIFOLD (OUTLINE) KENCO MODEL KMK-75-F		
DATE: 02-12-14	SHEET: 1 OF 2	DRAWING NUMBER
DRN. BY: RDM	CHKD. BY: DM	C-69155
SCALE: NONE	REVISION: A	