ø0.540" – O-RING SEAL MATERIAL DESIGNATIONS: A=AFLAS; B=BUNA-N; E=ETHYLENE PROPYLENE; V=FLUOROCARBON; K=KALREZ 9" STANDARD (CUSTOMER SPECIFIED UP TO 24") 3/4" NPT PROCESS CONNECTION 
 REV.
 DATE
 BY

 A
 10-29-04
 DS
 w 04-01-08 DS 18" STD. (REF.) (UP TO 33"(REF.)) - ECN N N  $6\frac{1}{2}$ " (APPROX.) ADDED: (CUSTOMER SPECIFIED UP TO 24")
ADDED: (UP TO 33" (REF.)); 18" WAS 17-1/2";
6-1/2" WAS 6" EXPLANATION:
SAFETY LINE WAS SASH CHAIN; ADDED FLOW ARROW; OAL WAS 17-1/4", MAX INS. WAS 8 3/4" 1" WRENCH FLATS

COMPRESSION NUT
WITH INTERNAL
O-RING SEAL SAFETY LINE -INJECTOR, RETRACTABLE (OUTLINE DWG) HC-276 BODY,
ALLOY 20 VALVE, W/CHECK VALVE, NO BODY BLEED,
MODEL KRINJ-75-HC-9-A20-CVN-(SEAL MAT'L)

DATE: 06-08-04 | SHEET: 1 OF 1 | DRAWING NUMBER DRN. BY: PMM SCALE: NONE KENCO ENGINEERING COMPANY DIMENSIONAL NOTE:
DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY
AND ARE SUBJECT TO CHANGE AT ANY TIME
WITHOUT NOTICE. WRENCH FLATS **₹** TULSA, OKLAHOMA CHKD. BY: REVISION: 27 w B-47182 1/2" FNPT CHEMICAL CONNECTION