



DIMENSIONAL NOTE:  
 DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY  
 AND ARE SUBJECT TO CHANGE AT ANY TIME  
 WITHOUT NOTICE.

O-RING SEAL MATERIAL DESIGNATIONS:  
 A=ATLAS; B=BUNA-N; E=ETHYLENE PROPYLENE;  
 V=FLUOROCARBON; K=KALREZ

REV.	DATE	BY	ECN	EXPLANATION:
A	10-29-04	DS	-	SAFETY LINE WAS SASH CHAIN; ADDED FLOW ARROW; OAL WAS 17-1/4"; MAX INS. WAS 10-1/2"
B	03-31-08	DS	N/A	MOVED SAFETY LINE FROM COMP. SEAL SIDE OF VALVE; ADDED: (CUSTOMER SPECIFIED UP TO 24") ; ADDED: (UP TO 30-3/4" (REF.))

  

<b>KENCO ENGINEERING COMPANY</b> TULSA, OKLAHOMA		INJECTOR, RETRACTABLE (OUTLINE DRAWING) 316 SS BODY, BRASS VALVE, w/CHECK VALVE, w/BODY BLEED, MODEL KRINJ-75-S6-10.75-B-CVB-(SEAL MAT'L)
DATE: 06-08-04	SHEET: 1 OF 1	DRAWING NUMBER
DRN. BY: PMM	CHKD. BY:	B-47178
SCALE: NONE	REVISION: B	