



DIMENSIONAL NOTE:
 DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY
 AND ARE SUBJECT TO CHANGE AT ANY TIME
 WITHOUT NOTICE.

O-RING SEAL MATERIAL DESIGNATIONS:
 A=AFLLAS; B=BUNA-N; E=ETHYLENE PROPYLENE;
 V=FLUOROCARBON; K=KALREZ

REV.	DATE	BY	ECN	EXPLANATION:
A	10-20-04	DS	N/A	SAFETY LINE WAS SASH CHAIN; ADDED FLOW ARROW; OAL WAS 17-1/4"; MAX INS. WAS 10-1/2"
B	03-31-08	DS	N/A	MOVED SAFETY LINE FROM COMP. SEAL SIDE OF VALVE; ADDED TOP VIEW; ADDED "CUSTOMER SPECIFIED UP TO 24"; ADDED "UP TO 30-3/4" (REF.)"

KENCO ENGINEERING COMPANY		INJECTOR, RETRACTABLE, (OUTLINE DRAWING) 316 SS BODY, BRASS VALVE, w/CHECK VALVE, NO BODY BLEED, MODEL KRINU-75-S6-10.75-B-CVN-(SEAL MAT'L)
TULSA, OKLAHOMA		DATE: 06-08-04
DRN. BY: PMM	CHKD. BY:	SHEET: 1 OF 1
SCALE: NONE	REVISION: B	DRAWING NUMBER
		B-47175