


**SWITCH SPECIFICATIONS:**

- SWITCH CONTACT CIRCUITRY: S.P.S.T. NORMALLY OPEN NON-LATCHING
- MAXIMUM TEMPERATURE: 221° F (105° C)
- MAXIMUM VOLTAGE: 100 VDC; 140 VAC
- MAXIMUM CURRENT: 0.25 AMPS DC; 0.18 AMPS AC
- MAXIMUM POWER: 7 WATTS

**NOTE:** REFER TO 75498 FOR 9959 INSTALLATION INSTRUCTIONS.

AGENCY APPROVAL	
CL. I, GRP. C,D	 CL. II, GRP. E,F,G LISTED <b>INDUSTRIAL CONTROL EQUIPMENT FOR HAZARDOUS LOCATIONS 5L14</b>

**DIMENSIONAL NOTE:**  
ALL DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY AND ARE SUBJECT TO CHANGE AT ANY TIME WITHOUT NOTICE.

INFORMATION IS PROPRIETARY TO KENCO ENGINEERING CO.

REV.	DATE	BY	CHKD.	ECN	EXPLANATION:
A	07-15-91	RC	RDM	N/A	221° F WAS 212° F; 18" LG. WIRE LEADS WERE 4" LG.; ADDED 18 GA.; REMOVED P/N 10002 DECAL
B	04-22-16	RDM	KLM	000280	REDRAWN; ITEM 4 P/N WAS 16207; ADDED SHEET 2; SHEET 2 WAS DWG. NO. B-9981; ADDED MTG. CLAMPS & PACKAGING TO BOM

KENCO ENGINEERING COMPANY TULSA, OKLAHOMA		
SWITCH, NON-LATCHING (S.P.S.T. N.O.) MODEL NO. 9959 FOR KENCO MLG'S		
DATE: 12-01-89 DRN. BY: ALH SCALE: 1"=1"	SHEET: 1 OF 2 CHKD. BY: RDM REVISION: B	DRAWING NUMBER B-9959