

REFERENCE NOTE:

MOUNTING FLANGES WITH (4) BOLT HOLES ARE OFFSET 45° FROM CENTERLINE OF GAUGE AND MOUNTING FLANGES WITH (8) BOLT HOLES ARE OFFSET 22.5° FROM CENTERLINE OF GAUGE


GENERAL NOTE:

PIPE PLUG IN OPTIONAL DRAIN PORT IS INSTALLED USING PTFE TAPE.

DIMENSIONAL NOTE:

ALL DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY AND ARE SUBJECT TO CHANGE AT ANY TIME WITHOUT NOTICE.

KMLG-F



INFORMATION IS PROPRIETARY TO KENCO ENGINEERING CO.

REV.	DATE	BY	CHKD.	ECN	EXPLANATION:	KENCO ENGINEERING COMPANY
Α	01-12-23	RDM	DM	N/A	REDRAWN; ADDED FRONT VIEW & END VIEW	TULSA, OKLAHOMA
						GAUGE, MAGNETIC LEVEL
						(OUTLINE DRAWING) MODEL KMLG-F
						DATE: 02-03-03 SHEET: 1 OF 1 DRAWING NUMBER
						DRN. BY: DPS CHKD. BY: RDM 43684
						SCALE: 1"=3" REVISION: A