

Certificate of Compliance

Certificate:

1921070

Contract: 239933

Project:

1921070

Issued: June 7, 2007

Issued to:

Kenco Engineering Company Post Office Drawer 470426

Tulsa, OK 74147

USA

Attn: Mr. Dan Dever

The products listed below are eligible to bear the CSA Mark shown



Issued by:

Nancy Szabo

Authorized by: Len Candeloro

Product Group Manager

PRODUCTS

CLASS 2258 02 PROCESS CONTROL EQUIPMENT For Hazardous Locations

Class I, Div 1, Groups B, C, and D; Class II, Div 1, Groups E, F nd G; Class III, Div 1; Type 4:

- Microtuf Series Thermal Differential Point Level Switch, Models KTDL-XXX-XXX-XXX.X-XXX-LE-XX (with integral Probe); or Remote version, Model KTDL-000-00-00000-XXX-RE-XX with Remote Probe, Model KTDL-XXX-XX-XXX.X-000-RP-XX; input rated 24/110/220V ac, 50/60Hz, 200/85/42mA; 24V dc, 100mA; relay contact rating 250V ac, 5A max; Temp Code T4C @ Max ambient 40 Deg C; MWP 3000 psi.
- Microtuf Series Thermal Differential Mass Flow Switch, Models KTDF-XXX-XXX-XXX.X-XXX-LE-XX (with integral Probe); or Remote version, Model KTDF-000-00-00000-XXX-RE-XX with Remote Probe, Model KTDF-XXX-XX-XXX.X-000-RP-XX; input rated 24/110/220V ac, 50/60Hz, 200/85/42mA; 24V dc, 100mA; relay contact rating 250V ac, 5A max; Temp Code T4C @ Max ambient 40 Deg C; MWP 3000 psi.

O:\ml\215782 Pepperl.doc\mek DQD 507WD 2002/03/01



Notes:

- 1. The suffixes "4X", "SH" or "SW" in the last position of the model code, indicate that the assembly is rated enclosure Type 4X.
- 2. If the process fluid temperature exceeds 40 Deg C, the device can not be used in a process atmosphere that has an ignition temperature of 120 Deg C increased by the difference of the fluid temperature and 40 Deg C.

APPLICABLE REQUIREMENTS

CSA Std C22.2 No 25-1966 - Enclosures for Use in Class II, Groups E, F and G Hazardous Locations

CSA Std C22.2 No 30-M1986 - Explosion-Proof Enclosures for Use in Class I Hazardous Locations

CAN/CSA-C22.2 No 94-M91 - Special Purpose Enclosures CSA Std C22.2 No 142-M1987 - Process Control Equipment

MARKINGS

The CSA Mark, the company name, and/or tradename/ or identification/ or file number 239933, model designation, and any 'Cautions' or other information as specified in the Certification Report.