



MODEL NO.: NFS-11  
 DRAWING NO.: C-19318  
 DESCRIPTION: NFS WITH STANDARD SPRING FOR FLOW RATES OF 6 OR MORE DROPS PER MINUTE.

NFS-11L  
 C-19318-L  
 NFS WITH LIGHT SPRING FOR FLOW RATES BETWEEN 3 AND 6 DROPS PER MINUTE.

NOTE: SWITCH MUST BE MOUNTED TERMINAL END UP WITH A MINIMUM ANGLE OF 20° OFF HORIZONTAL TO PREVENT CONDENSATION AROUND SWITCH CONTACT.

DIMENSIONAL NOTE:  
 ALL DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY AND ARE SUBJECT TO CHANGE AT ANY TIME WITHOUT NOTICE.

REV.	DATE	BY	CHKD.	ECN	EXPLANATION:
E	11-24-14	RDM	KLM	000233	REDRAWN; UPDATED TO REFLECT ITEM 12 REDESIGN; ADDED SUFFIX "-BLK" TO O-RING PART NUMBERS; MOVED 13013-V O-RING TO 802 SUBASSEMBLY; ADDED ENGRAVING OPTION TO LASER ETCHING
					NOTE; ADDED NOTE TO PRESSURE TEST NFS-11L TO 2000 FOR 8 MINUTES

INFORMATION IS PROPRIETARY TO KENCO ENGINEERING CO.

TOLERANCES UNLESS OTHERWISE SPECIFIED  
 DECIMAL: ±.005" FRACTIONAL: ±1/64" ANGULAR: ±1/2"

**KENCO ENGINEERING COMPANY**  
 TULSA, OKLAHOMA

SWITCH, NO FLOW  
 MODEL NFS-11 / NFS-11L

DATE: 02-05-93 SHEET: 1 OF 2 DRAWING NUMBER  
 DRN. BY: RC CHKD. BY: NA C-19318  
 SCALE: 1"=1" REVISION: E C-19318-L