



MODEL NO.: NFS-6
 DRAWING NO.: C-19315
 DESCRIPTION: NFS WITH STANDARD SPRING FOR FLOW RATES OF 6 OR MORE DROPS PER MINUTE.

NFS-6L
 C-19315-L
 NFS WITH LIGHT SPRING FOR FLOW RATES BETWEEN 3 AND 6 DROPS PER MINUTE.

DIMENSIONAL NOTE:
 ALL DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY AND ARE SUBJECT TO CHANGE AT ANY TIME WITHOUT NOTICE.

NOTE: SWITCH MUST BE MOUNTED TERMINAL END UP WITH A MINIMUM ANGLE OF 20° OFF HORIZONTAL TO PREVENT CONDENSATION AROUND SWITCH CONTACT.

REV.	DATE	BY	CHKD.	ECN	EXPLANATION:
E	11-24-14	RDM	KLM	000233	REDRAWN; UPDATED TO REFLECT ITEM 12 REDESIGN; ADDED SUFFIX "-BLK" TO O-RING PART NUMBERS; MOVED 13013-V O-RING TO 802 SUBASSEMBLY; ADDED ENGRAVING OPTION TO LASER ETCHING
					NOTE: ADDED NOTE TO PRESSURE TEST NFS-6L TO 2000 FOR 8 MINUTES

INFORMATION IS PROPRIETARY TO KENCO ENGINEERING CO.

TOLERANCES UNLESS OTHERWISE SPECIFIED
 DECIMAL: ±.005" FRACTIONAL: ±1/64" ANGULAR: ±1/2°

KENCO ENGINEERING COMPANY
 TULSA, OKLAHOMA

SWITCH, NO FLOW
 MODEL NFS-6 / NFS-6L

DATE: 02-05-93 SHEET: 1 OF 2 DRAWING NUMBER
 DRN. BY: RC CHKD. BY: NA C-19315
 SCALE: 1"=1" REVISION: E C-19315-L