



MODEL NO.: KEFS-2-SPDT5-400

SPECIFICATIONS:

SWITCH RATING: 5A @ 125/250 VAC

0.3A @ 125 VDC

CONTACT TYPE: SPDT

MINIMUM OPERATING S.G.: .53

MAX. WORKING PRESSURE: 2000 PSI

TEMPERATURE LIMIT: 400°F

WETTED MATERIALS: 303/304 STAINLESS STEEL.

	2/19/13 BRC	BLUE WIRE (NORMALLY CLOSED) WAS (NORMALLY OPEN)	DIM'S IN INCHES		$\overline{\bigcirc}$	MATERIA	-:	SEE B/M
	N/A RDM	RED WIRE (NORMALLY OPEN) WAS (NORMALLY CLOSED)	TOLERANCES UNLESS OTHERWISE SPECIFIED.	\square		RELEASE	LEVEL:	RELEASED
А	06/21/12 BRC N/A DS	RELEASED	ANGULAR ±1/2° FRACTIONAL ±1/64"		EERING lahoma USA	DRAWIN	G CREATED	IN PRO/ENGINEER
REV	DATE DRN. ECN CHKD.	DESCRIPTION	$(X.XXX)$ ± 0.005 "	SWITCH,ELEC		O PSI 5A SP	DT HIGH TE 0.750	MP KEFS (OUTLINE DWG) DRAWING NUMBER
ENG	INEERING CO. AND SHALL	VING AND THE INFORMATION CONTAINED HEREIN IS PROPRIETARY TO KENCO NOT BE REPRODUCED, COPIED, OR DISCLOSED IN WHOLE OR IN PART, OR USED Y OTHER PURPOSE WITHOUT THE WRITTEN PERMISSION OF KENCO ENGINEERING.	MACH FILLET RAD031" 125 MAX. FINISH, ALL MACHINED SURFACES.	CHKD. BY:		REVISION: SHEET I O	B F 3	65302