



RELIEF PRESSURE ADJUSTMENT RANGE: 0 TO 150 PSI
 RELIEF PRESSURE FACTORY SETTING: 50 PSI

WETTED MATERIALS:
 BODY: PVC
 DIAPHRAGM: TEFLON (WETTED)/EPDM (NON-WETTED)

NON-WETTED MATERIALS:
 SPRING CASE: PVC
 RELIEF PRESSURE ADJUSTING SCREW: PVC
 SPRING: ZINC PLATED SPRING STEEL
 NUTS, BOLTS & WASHERS: 18-8 STAINLESS STEEL

MODEL NUMBER:
 KBPV-T-50-P-P-TE (THREADED CONNECTIONS)
 KBPV-S-50-P-P-TE (SOCKET WELD CONNECTIONS)

B	5/20/15	LR	REVISED TO SHOW LABEL CHANGE	DIM'S IN INCHES TOLERANCES UNLESS OTHERWISE SPECIFIED.	 Tulsa, Oklahoma USA	MATERIAL:	SEE B/M	
	N/A	BRC				RELEASE LEVEL:	RELEASED	
A	5/05/15	BRC	RELEASED	ANGULAR ±1/2° FRACTIONAL ±1/64" (X.X) ±0.015" (X.XX) ±0.010" (X.XXX) ±0.005" MACH FILLET RAD: .031" 125 MAX. FINISH, ALL MACHINED SURFACES.	DRAWING CREATED IN PRO/ENGINEER	TITLE:		
	N/A	KLM				VALVE, KBPV RELIEF, 1/2", BOLTED	DRN. BY: BRC	SCALE: 0.600
REV.	DATE	DRN.	DESCRIPTION		 Tulsa, Oklahoma USA	CHKD. BY: -	REVISION: B	73407
	ECN	CHKD.				DATE: 05-03-18	SHEET 1 OF 3	

PROPRIETARY: THIS DRAWING AND THE INFORMATION CONTAINED HEREIN IS PROPRIETARY TO KENCO ENGINEERING CO. AND SHALL NOT BE REPRODUCED, COPIED, OR DISCLOSED IN WHOLE OR IN PART, OR USED FOR MANUFACTURE OR FOR ANY OTHER PURPOSE WITHOUT THE WRITTEN PERMISSION OF KENCO ENGINEERING.