



RELIEF PRESSURE ADJUSTMENT RANGE: 0 TO 150 PSI  
RELIEF PRESSURE FACTORY SETTING: 50 PSI

WETTED MATERIALS:

BODY: PVC  
DIAPHRAGM: TEFLON (WETTED)/EPDM (NON-WETTED)

NON-WETTED MATERIALS:

SPRING CASE: PVC  
RELIEF PRESSURE ADJUSTING SCREW: PVC  
SPRING: ZINC PLATED SPRING STEEL  
NUTS, BOLTS & WASHERS: 18-8 STAINLESS STEEL

MODEL NUMBER:

KPRV-T-50-P-P-TE (THREADED CONNECTIONS)  
KPRV-S-50-P-P-TE (SOCKET WELD CONNECTIONS)

B	5/20/15	LR	REVISED TO SHOW LABEL CHANGE	DIM'S IN INCHES TOLERANCES UNLESS OTHERWISE SPECIFIED.	<b>KENCO</b> ENGINEERING Tulsa, Oklahoma USA	MATERIAL:	SEE B/M	
	N/A	BRC				RELEASE LEVEL:	RELEASED	
A	5/05/15	BRC	RELEASED	ANGULAR ±1/2° FRACTIONAL ±1/64" (X.X) ±0.015" (X.XX) ±0.010" (X.XXX) ±0.005" MACH FILLET RAD: .031" 125 MAX. FINISH, ALL MACHINED SURFACES.	DRAWING CREATED IN PRO/ENGINEER			
	N/A	KLM			TITLE: VALVE, KPRV RELIEF, 1/2", BOLTED			
REV.	DATE	DRN.	DESCRIPTION	DRN. BY: BRC		SCALE:	0.600	DRAWING NUMBER
	ECN	CHKD.		CHKD. BY: KLM		REVISION:	B	
<b>PROPRIETARY:</b> THIS DRAWING AND THE INFORMATION CONTAINED HEREIN IS PROPRIETARY TO KENCO ENGINEERING CO. AND SHALL NOT BE REPRODUCED, COPIED, OR DISCLOSED IN WHOLE OR IN PART, OR USED FOR MANUFACTURE OR FOR ANY OTHER PURPOSE WITHOUT THE WRITTEN PERMISSION OF KENCO ENGINEERING.				DATE:	5/05/15	SHEET 1 OF 3	73406	